

# technical brief

The Esplanade Co Ltd 1 Esplanade Drive Singapore 038981 Tel (65) 6828 8222 Fax (65) 6336 6889 www.esplanade.com



# **THEATRE**

STAGE	BACKSTAGE
SEATING CAPACITY	LOADING DOCK
Total Capacity 1,948 seats (with Proscenium box seats held)	Accessed from Raffles Avenue. The Theatre's Rear and Side stages are directly accessed via two loading bays in the adjacent scenery store.
Capacity reduced by use of the following:  Small pit / Thrust stage 21 seats  Medium pit / Thrust stage 74 seats  Large pit / Thrust stage 131 seats  Cockpit Sound console deployed in auditorium 19 seats	Loading Dock Entrance Clear Height  Dock Height from floor  Loading Bay Openings (x2)  Door from Scenery Store to Rear Stage  Door from Scenery Store to Side Stage  4.2 m  1.13 m  2.5m (w), 3.5m (h)  5.1m(w), 9.1m (h)  5.1m (w), 9.1m (h)
FEATURES	DRESSING ROOMS
Floor Black painted tempered Weathertex stage floor Information regarding trapped sections is available upon request.	Each is equipped with make-up mirrors and tables, full length mirrors, telephones, sinks, toilets and showers with hot and cold running water, audio monitoring and paging systems.
Main Stage 38.8 (w) x 23.6m (d)	On Level 1 (Stage Level)
Side Stage* 17.1m (opening), 19m (w) x 18.8m (d), 10.4m (clear Rear Stage* 19.9m (opening), 23.9m (w) x 19.6m (d), 9.5m (clear Resilient Floor (Ballet wagon) 19m (w) x 19m (d)	
*Available with prior arrangement as the Side and Rear Stages house stock equipment. Removal and restoration of equipment is at the expense of the u	On Level B1 (Under Stage Level)
Proscenium Opening Hard Proscenium False Proscenium  16.3m (w) x 14m (h at centre), 13.5m (h at sides) Adjustable opening 13.1m - 18.6m (width)	2 no. Musician's changing room Can accommodate up to 15 persons, with 7 make-up stations  Other dressing rooms, visiting company office spaces/production offices may be available upon request, subject to users' requirements in the other venues.
Forestage Elevators Used as stage floor extension, auditorium seating area or orchestra pit.  1 elevator (Small pit) 18m (w) x 3m (d) 2 elevators (Medium pit) 18m (w) x 5m (d) 3 elevators (Large pit) 18m (w) x 7m (d)	(Note: The following facilities are shared with other performing venues.)  GREEN ROOM  Location Basement One Facilities Vending machines. Available to cast, crew & Esplanade staff
MUSICAL INSTRUMENTS	WARDROBE
Piano Inventory: 3 X Steinway D (9') Concert Grand 1 X Steinway B (7') Grand 1 X Steinway A (6') Grand 1 X Yamaha S6 (6') Grand 7 X Yamaha U5 Upright	Location Basement One Facilities Wardrobe maintenance room, Wig maintenance room, Laundry room with 2 washers & 2 dryers.  All wardrobe equipment shall be operated by Esplanade staff.
Use of pianos is subject to availability, therefore prior arrangement is essential.  Esplanade's resident piano technician must tune all pianos before ever public performance.  Tuning Rates available upon request.	ту

THEATRE (Technical Brief)
Subject to change –contact venue for latest information

Correct as of 07 April 2022 Page 1 of 2

#### **FLY SYSTEM**

### **HOUSE CURTAIN**

Colour. Red velour (Operation: Flys or Travels)

# RIGGING SYSTEM

**OPERATION** 

Control: Waagner-Biro CAT System Second Gallery Stage Left (PS) Location:

### **FLY LINESETS**

Quantity: 103 overstage battens including House Curtain Distribution: 200mm centres (Refer to Hanging Plot for specifics) Description: Prolyte Protrack battens with 48mm dia. bottom pipe

Length: 21m

Maximum Capacity: : WLL of 750kg (Uniformly Distributed Load)

Max SWL of 500kg for battens programmed to move

at full speed

300kg (Point load) Variable, 50-1700mm/sec

Max. Fly Height: 28.5m

### OTHERS (available on prior request):

250kg point hoists

Speed:

1000kg Prolyft chain hoists Concert Truss Systems

### **REAR STAGE FLY BARS**

10 - Permanently mounted in Rear Stage ceiling Quantity:

Distribution: Fixed @ 2m centres

Maximum Capacity: 500kg (Uniformly Distributed Load)

Fixed @ 0.2m/sec. Speed:

Max. Fly Height: 9.5m

### **LIGHTING**

### **LOCAL POWER SUPPLY**

230 Volt single phase, 50 Hz

## ADDITIONAL POWER

A 3-phase, 600-Amp distribution, is situated Mid-Stage Left (Prompt side). Connection is to bus bars, by 12mm bolt and the hirer should provide necessary, bare-end, lugs. Power connections, to isolators, are subject to inspection by a Licensed Electrical Worker (LEW) and the hirer must provide ELCB + overload protection.

# STANDARD RIG

A standard pre-focused lighting rig exists FOH-only. There is no standard light rig overstage - it is a bare rig.

Onstage lighting must be set for each production and all expenses for the setup and subsequent strike are to be borne by the user.

### **CONTROL & CONSOLE**

The Theatre Lighting System is controlled by a grandMA2 Full-Size Computerised Control System with a grandMA2 Network Processor Unit (NPU), grandMA2 Replay Unit (RPU) and a MA onPC tracking backup

All systems have 4096 parameters and use the MA-Net2 Protocol over Ethernet System for DMX-512 distribution

# **DIMMERS**

400 x 2.4kW dimmers 100 x 5kW dimmers

100 x 2.4kW non-dimmed outlets

# SOUND

### LOCAL POWER SUPPLY

Situated Downstage Left (Prompt side)

230 Volt 50 Hz

125 Amp 3 phase C-form outlet with isolated earth.

63 Amp 1 phase

#### **MIXERS**

Control Room: Stagetec Crescendo digital console

Cockpit: Digico SD7

Cockpit elevator wagon, located at Rear Center stalls.

Front Width 3.6 m Rear Width 4.5 m Depth 2.2 m

### **MICROPHONES & MIC STANDS**

An assortment of microphones and radio-microphones is available. List upon request as microphones are shared across all venues.

Wireless miniature microphone capsules are available on request and rental charges apply.

Any microphones that cannot be catered for are to be brought in by the

### **DEFAULT FOH SPEAKERS**

d&b audiotechnik C7 installed systems comprising of Left, Centre, Right Main Clusters and Fill Systems.

### **ACOUSTIC FEATURES**

Auditorium has remotely deployable Acoustic Banners for Amplified applications.

# COMMUNICATIONS

Stage Manager's desk, Cuelights & Accessories, Intercom & Accessories, Video Cameras & Accessories, Video Monitors & Accessories, Assisted Listening system, & Supertitles System.

### LIGHTING CONT'D

# **CONNECTOR TYPE**

16 Amp, CEE17

# **EQUIPMENT**

Onstage is a selection of 750W Source 4s and 600W SL profile luminaries, 2 and 5 kW fresnels, 2.5 kW PCs and 1kW Iris 4 Cyc Floods, some of the fixtures may be fitted with Rainbow colour scrollers.

These are complemented with Martin Mac 2000 Washes, Profiles and Performances

Other effects can be arranged as required.

### **FOLLOWSPOTS**

4x RJ Cyrano 2.5kW HMI 3/8°

THEATRE (Technical Brief) Correct as of 07 April 2022 Page 2 of 2